

Tire Sizes and Specifications: **Dayton Quadra LTE**

▶ **PRINT PRODUCT SHEET**

Size	Service Description	Load Range	Speed Rating	SideWall Styling	Article Number	Approved Rim Widths	Measuring Rim Width	Overall Tire Diameter	Overall Section Width	Tread Width	Static Load Radius	Tread Depth (32")	RPM	RPK	Tire Weight	Limited Mileage Warranty	Limited Warranty (Kilometres)	UTQG
P185/75R14	89S		S	WS	021-199	4.5-6.0	(5.0)	25.0	7.2	5.3	11.2	11	833	518	18	65000	105000	520 A B
P195/75R14	92S		S	WS	021-202	5.0-6.5	(5.5)	25.5	7.7	5.7	11.4	11	817	506	19	65000	105000	520 A B
P205/75R14	95S		S	WS	021-210	5.0-7.0	(5.5)	26.1	8.0	6.1	11.6	11	798	495	20	65000	105000	520 A B
P205/75R15	97S		S	WS	021-229	5.0-7.0	(5.5)	27.1	8.0	6.1	12.1	11	769	477	21	65000	105000	520 A B
P205/75R15	97S		S	RWL	028-452	5.0-7.0	(5.5)	27.1	8.0	6.1	12.1	11	769	477	21	65000	105000	520 A B
P215/75R15	100S		S	WS	021-237	5.5-7.0	(6.0)	27.7	8.5	6.4	12.4	11	752	468	24	65000	105000	520 A B
P225/75R15	102S		S	WS	021-245	6.0-7.5	(6.0)	28.3	8.8	6.6	12.6	11	736	457	25	65000	105000	520 A B
P235/75R15	105S		S	WS	021-253	6.0-8.0	(6.5)	28.9	9.3	6.9	12.8	12	721	447	28	65000	105000	520 A B
P235/75R15	105S		S	RWL	028-444	6.0-8.0	(6.5)	28.9	9.3	6.9	12.8	12	721	447	27	65000	105000	520 A B
P235/75R15 XL	108S	XL	S	BW	069-337	6.0-8.0	(6.5)	28.9	9.3	6.9	12.8	12	721	447	29	65000	105000	520 A B
P185/70R14	87S		S	WS	021-261	4.5-6.0	(5.5)	24.3	7.4	5.2	11.0	10	857	532	17	65000	105000	520 A B
P195/70R14	90S		S	WS	021-288	5.0-6.5	(6.0)	24.8	7.9	5.5	11.1	10	840	521	18	65000	105000	520 A B
P205/70R14	93S		S	WS	021-296	5.0-7.0	(6.0)	25.4	8.2	5.8	11.4	11	820	508	19	65000	105000	520 A B
P215/70R14	96S		S	WS	021-326	5.5-7.0	(6.5)	25.9	8.7	6.1	11.6	11	804	498	20	65000	105000	520 A B
P205/70R15	95S		S	WS	021-342	5.0-7.0	(6.0)	26.3	8.2	5.8	11.8	11	792	491	20	65000	105000	520 A B
P215/70R15	97S		S	WS	021-350	5.5-7.0	(6.5)	26.9	8.7	6.1	12.1	11	774	481	22	65000	105000	520 A B

P225/70R15	100S		S	WS	021-369	6.0-7.5	(6.5)	27.4	9.0	6.4	12.3	11	760	472	25	65000	105000	520 A B
P175/65R14	81S		S	BW	039-098	5.0-6.0	(5.0)	23.0	7.0	5.2	10.5	11	906	555	15	65000	105000	520 A B
P185/65R14	85S		S	BW	039-101	5.0-6.5	(5.5)	23.5	7.4	5.5	10.7	11	886	550	16	65000	105000	520 A B
P195/65R14	88S		S	BW	039-128	5.5-7.0	(6.0)	24.0	7.9	5.9	10.9	11	868	538	17	65000	105000	520 A B
P195/65R15	89S		S	BW	058-440	5.0-7.0	(6.0)	25.00	7.91	5.92	11.3	11	833	517	19	65000	105000	520 A B
P205/65R15	92S		S	BW	024-031	5.5-7.5	(6.0)	25.5	8.2	6.7	11.6	11	817	506	19	65000	105000	520 A B
P215/65R15	95S		S	BW	058-459	6.0-7.5	(6.5)	26.0	8.7	6.3	11.8	10	801	497	21	65000	105000	520 A B
215/65R16	98T		T	BW	097-209	6.0-7.5	(6.5)	26.0	8.7	6.3	11.9	11	801	498	22	65000	105000	520 A B
P215/60R16	94S		S	BW	058-424	6.0-7.5	(6.5)	26.1	8.7	6.5	11.9	11	798	494	22	65000	105000	520 A B
P225/60R16	97S		S	BW	058-432	6.0-8.0	(6.5)	26.0	9.0	6.8	11.8	11	783	486	23	65000	105000	520 A B
P205/55R16	89S		S	BW	058-637	5.5-7.5	(6.5)	24.9	8.4	6.7	11.5	10	837	520	20	65000	105000	520 A B