

Tire Sizes and Specifications: **Firestone FR380**

[▶ PRINT PRODUCT SHEET](#)

Size	Service Description	Speed Rating	SideWall Styling	Article Number	Approved Rim Widths	Measuring Rim Width	Overall Tire Diameter	Overall Section Width	Tread Width	Static Load Radius	Tread Depth (32")	RPM	RPK	Tire Weight	Limited Mileage Warranty	Limited Warranty (Kilometres)	UTQG
P155/80R13	79S	S	WS	097-624	4.0-5.0	(4.5)	22.8	6.2	3.9	10.3	9	914	568	13	55000	90000	400 A B
P165/80R13	83S	S	WS	097-659	4.0-5.5	(4.5)	23.4	6.5	4.2	10.5	9	890	553	14	55000	90000	400 A B
P175/80R13	86S	S	WS	097-756	4.5-6.0	(5.0)	24.0	7.0	4.5	10.7	10	868	539	15	55000	90000	400 A B
P185/80R13	90S	S	WS	097-969	4.5-6.0	(5.0)	24.7	7.2	4.8	11.0	10	843	524	16	55000	90000	400 A B
P185/75R14	89S	S	WS	097-942	4.5-6.0	(5.0)	25.0	7.2	4.8	11.2	10	833	518	17	55000	90000	400 A B
P195/75R14	92S	S	WS	098-000	5.0-6.5	(5.5)	25.5	7.7	5.0	11.4	10	817	508	19	55000	90000	400 A B
P205/75R14	95S	S	WS	098-043	5.0-7.0	(5.5)	26.1	8.0	5.3	11.6	10	798	496	19	55000	90000	400 A B
P215/75R14	98S	S	WS	098-167	5.5-7.0	(6.0)	26.7	8.5	5.6	11.9	10	780	485	21	55000	90000	400 A B
P205/75R15	97S	S	WS	098-051	5.0-7.0	(5.5)	27.1	8.0	5.3	11.8	10	769	478	21	55000	90000	400 A B
P215/75R15	100S	S	WS	098-329	5.5-7.0	(6.0)	27.7	8.5	5.6	12.4	10	752	467	23	55000	90000	400 A B
P225/75R15	102S	S	WS	098-353	6.0-7.5	(6.0)	28.3	8.8	5.8	12.6	10	736	457	24	55000	90000	400 A B
P235/75R15	105S	S	WS	098-361	6.0-8.0	(6.5)	28.9	9.3	6.1	12.8	10	721	448	27	55000	90000	400 A B
P175/70R13	82S	S	BW	097-705	4.5-6.0	(5.0)	22.7	7.0	4.8	10.2	10	918	570	14	55000	90000	400 A B
P175/70R14	84S	S	BW	097-713	4.5-6.0	(5.0)	23.7	7.0	4.8	10.7	10	879	546	15	55000	90000	400 A B
P215/70R14	96S	S	WS	098-078	5.5-7.0	(6.5)	25.9	8.7	5.8	11.6	10	804	500	20	55000	90000	400 A B

P205/70R15	95S	S	WS	098-035	5.0-7.0	(6.0)	26.3	8.2	5.6	11.8	10	792	492	19	55000	90000	400 A B
P215/70R15	97S	S	WS	098-116	5.5-7.0	(6.5)	26.9	8.7	5.8	12.1	10	774	481	22	55000	90000	400 A B
185/70R13	85S	S	BW	148-087	4.5-6.0	(5.5)	23.2	7.4	5.0	10.4	10	898	558	15	55000	90000	400 A B
185/70R14	87S	S	BW	148-104	4.5-6.0	(5.5)	24.3	7.4	5.0	11.0	10	857	533	16	55000	90000	400 A B
195/70R14	90S	S	BW	148-138	5.0-6.5	(6.0)	24.8	7.9	5.3	11.1	10	840	522	17	55000	90000	400 A B
205/70R14	93S	S	WS	148-155	5.0-7.0	(6.0)	25.4	8.2	5.6	11.4	10	820	510	18	55000	90000	400 A B
175/65R14	81S	S	BW	148-189	5.0-6.0	(5.0)	23.0	7.0	5.3	10.5	10	906	563	15	55000	90000	400 A B
185/65R14	85S	S	BW	148-206	5.0-6.5	(5.5)	23.5	7.4	5.6	10.7	10	886	551	16	55000	90000	400 A B
P195/65R15	89S	S	BW	061-940	5.5-7.0	(6.0)	25.0	7.9	5.8	11.4	11	833		18	55000	90000	400 A B
P205/65R15	92S	S	BW	098-019	5.5-7.5	(6.0)	25.5	8.2	5.8	11.6	10	817	508	18	55000	90000	400 A B
P215/65R15	95S	S	BW	061-957	6.0-7.5	(6.5)	26.0	8.7	6.4	11.7	11	801		22	55000	90000	400 A B
215/65R16	98T	T	BW	061-974	6.0-7.5	(6.5)	27.0	8.7	6.3	12.3	11	772		24	55000	90000	400 A B
P215/60R16	94S	S	BW	061-991	6.0-7.5	(6.5)	26.1	8.7	6.5	11.9	11	798		23	55000	90000	400 A B
P225/60R16	97S	S	BW	062-008	6.0-8.0	(6.5)	26.6	9.0	6.8	12.1	12	783		24	55000	90000	400 A B