

Tire Sizes and Specifications: **Dayton Timberline A/T**

[▶ PRINT PRODUCT SHEET](#)

Size	Load Range	SideWall Styling	Article Number	Approved Rim Widths	Measuring Rim Width	Overall Tire Diameter	Overall Section Width	Tread Width	Static Load Radius	Tread Depth (32")	RPM	RPK	Tire Weight	UTQG	Notes
P195/75R14	SL	OWL	132-330	5.0-6.5	(5.5)	25.5	7.7	5.8	11.4	12	817	513	20	440 B C	+
P205/75R15	SL	OWL	064-440	5.0-7.0	(5.5)	27.1	8.0	6.1	12.1	12	769	484	21	440 B C	
P215/75R15	SL	OWL	064-459	5.5-7.0	(6.0)	27.7	8.5	6.5	12.4	13	752	474	23	440 B C	
P225/75R15	SL	OWL	064-467	6.0-7.5	(6.0)	28.3	8.8	6.7	12.6	13	736	463	26	440 B C	
P235/75R15	SL	OWL	064-475	6.0-8.0	(6.5)	28.9	9.3	6.9	12.8	14	721	454	30	440 B C	
P235/75R15 XL	XL	OWL	064-483	6.0-8.0	(6.5)	28.9	9.3	6.9	12.8	14	721	454	31	440 B C	
P265/70R17	SL	OWL	073-148	7.0-9.0	(8.0)	31.7	10.7	8.0	14.1	12	657	409	39	440 B C	*
P235/70R15	SL	OWL	073-091	6.0-8.0	(7.0)	28.0	9.5	6.9	12.5	12	744	462	29	440 B C	*
P225/70R14	SL	OWL	066-435	5.0-7.5	(6.5)	26.5	9.0	6.6	11.8	13	786	495	25	440 B C	
P235/70R16	SL	OWL	102-490	6.0-8.0	(7.0)	29.0	9.5	6.9	13.0	12	718		29	440 B C	
P255/70R16	SL	OWL	102-512	6.5-8.5	(7.5)	30.1	10.2	7.5	13.4	12	692		34	440 B C	
LT235/85R16	E	OWL	282-073	6.0-7.0	(6.5)	31.7	9.3	6.8	14.0	14	657		43		+
LT255/85R16	D	OWL	282-014	6.5-8.0	(7.0)	33.1	10.0	7.5	14.6	15	629	373	48		+
LT235/75R15	C	OWL	299-189	6.0-7.0	(6.5)	28.9	9.3	6.9	12.8	14	721	463	34		
LT225/75R16	D	BW	299-219	6.0-7.0	(6.0)	29.3	8.8	6.5	13.1	13	711	448	34		
LT245/75R16	E	BW	299-227	6.5-7.0	(7.0)	30.5	9.8	7.2	13.6	14	683	419	41		
LT245/75R16	C	OWL	150-436	6.5-7.0	(7.0)	30.5	9.8	7.2	13.6	14	683	424	41		*
LT265/75R16	D	OWL	299-596	7.0-8.0	(7.5)	31.7	10.5	7.8	14.0	15	657	398	44		
LT285/75R16	D	OWL	299-618	7.5-9.0	(8.0)	32.8	11.3	8.4	14.4	15	635	400	47		
27x8.50R14 LT	C	OWL	281-972	6.0-7.5	(7.0)	26.5	8.6	6.6	12.3	15	786	488	29		+
30x9.50R15 LT	C	OWL	299-243	6.5-8.5	(7.5)	29.5	9.5	7.3	13.7	15	706	436	36		
31x10.50R15 LT	C	OWL	299-251	7.0-9.0	(8.5)	30.5	10.5	8.1	14.1	15	683	418	40		

32x11.50R15 LT	C	OWL	299-278	8.0-10.0	(9.0)	31.5	11.4	8.8	14.5	17	661	401	46		
33x12.50R15 LT	C	OWL	299-286	8.5-11.0	(10.0)	32.5	12.5	9.6	14.9	17	641	383	53		
31x10.50R16.5 LT	D	OWL	281-980	8.25	(8.25)	30.5	10.5	8.1	14.2	15	683	418	42		+
33x12.50R16.5 LT	D	OWL	150-401	8.25-10.5	(9.75)	32.5	12.4	9.6	15.1	17	641	383	53		*
LT215/85R16	D	BW	299-197	5.5-7.0	(6.0)	30.4	8.5	6.3	13.5	13	685	421	34		
LT235/85R16	E	BW	299-200	6.0-7.0	(6.5)	31.7	9.3	6.8	14.0	14	657	398	41		
P245/75R16	SL	OWL	102-474	6.5-7.0	(7.0)	30.5	9.8	7.2	13.6	14	683	683	41	440 B C	
7.50R16 LT	D	BW	282-022	5.5-7.0	(6.0)	31.8	8.7	6.5	14.7	13	655	396	38		+
8.75R16.5 LT	D	BW	150-282	6.0-6.75	(6.75)	29.5	8.8	6.3	13.8	14	706	439	34		*

*Widetrack Baja A/T Design, +Widetrack Radial Baja A/T Design