

**SPORT PERFORMANCE****DUNLOP SP SPORT 5000™ &  
SP SPORT 5000™ DSST**ULTRA HIGH-PERFORMANCE  
ALL-SEASON TIRE

FEATURES	BENEFITS
• Innovative, asymmetrical tread design	• Optimum balance of wet and dry performance
• Large, stable, interconnected tread blocks	• Exceptional dry cornering, grip and stability
• Independent inner tread blocks with open shoulder grooves	• Maximize water dispersion and all-season grip
• Full-width, twin-cut steel belts with Jointless Band Technology ™	• Dependable ride uniformity and excellent footprint shape
• Exclusive, high-performance, all-season tread compound	• Optimizes grip, control, energy absorption and tread wear in a wide range of driving and weather conditions
• Max Flange Shield ™	• Protects rims from accidental curb damage
• Dunlop Self-Supporting Technology (DSST) features a patented sidewall construction and specially-developed compounds**	• Continued mobility up to a distance of 50 miles at a maximum speed of 50 mph in normal conditions**

\*\*Only on the SP Sport 5000 DSST.

**UNIQUE DUNLOP TECHNOLOGIES****™ Jointless Band Technology**

It maintains the tire's ideal shape at highway speeds. Nylon is positioned in all the right places to improve handling and tread wear. And unlike sheet cap plies, this one is spiral wound and doesn't have splices, which can lead to unwanted vibration.

**™ Max Flange Shield**

The rubber guard extends beyond the rim and wraps around the lower sidewall of the tire to protect rims from accidental curb damage.

SIZE	SERVICE DESC.	LOAD RANGE	SIDE-WALL	PRODUCT CODE	MATERIAL NUMBER	RIM WIDTH (IN)	APPRVD. RIM WIDTHS (IN)	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	STATIC LOADED RADIUS (IN)	REVS/ MILE	TREAD WIDTH (IN)	TREAD DEPTH (IN)	MAX. LOAD (LBS)	TIRE WEIGHT (LBS)	UTQG	OE FITMENT
<b>SP SPORT 5000</b>																	
P205/55ZR15	87W	SL	BSW	265037639	157707	6.5	5.5 - 7.5	8.5	23.8	10.9	872	7.5	10/32	1201	23.2		
P215/50ZR15	87W	SL	BSW	265037656	157711	7.0	6.0 - 7.5	8.8	23.5	10.8	885	7.8	10/32	1201	21.4		
P205/50ZR15	84W	SL	BSW	265014724	157710	6.5	5.5 - 7.5	8.4	23.1	10.6	899	7.2	10/32	1113	18.7		
P195/50ZR15	81W	SL	BSW	265014723	157709	6.0	5.5 - 7.0	7.9	22.7	10.5	914	6.9	10/32	1019	17.5		
P225/55ZR16	94W	SL	BSW	265037677	157715	7.0	6.0 - 8.0	9.3	25.7	11.8	809	7.9	10/32	1477	25.1		
P205/55ZR16	89W	SL	BSW	265037610	157714	6.5	5.5 - 7.5	8.5	24.8	11.4	836	7.5	10/32	1279	22.3		
P255/50ZR16	99W	SL	BSW	265014740	157719	8.0	7.0 - 9.0	10.4	26.1	11.9	799	9.5	10/32	1687	27.7		
P245/50ZR16	96W	SL	BSW	265014738	157718	7.5	7.0 - 8.5	9.9	25.7	11.8	811	9.1	10/32	1576	27.0		
235/50R16	95H	SL	BSW	265038537	157717	7.5	6.5 - 8.5	9.6	25.3	11.6	823	8.8	10/32	1521	25.6	280 A A	AUDI A6 (2.7L, 4.2L) 00-03
P225/50ZR16	91W	SL	BSW	265014736	157716	7.0	6.0 - 8.0	9.1	24.9	11.5	835	8.4	10/32	1367	24.2		
P195/50R16	83V	SL	BSW	265038952	173783	6.0	5.5 - 7.0	7.7	23.7	10.9	886	7.1	10/32	1074	20.1	360 A A	MAZDA PROTÉGÉ 01-03
P245/45ZR16	94W	SL	BSW	265014716	157720	8.0	7.5 - 9.0	9.8	24.8	11.4	839	8.8	10/32	1477	24.6		
255/60R17	106H	SL	VSB	265037661	193406	7.5	7.0 - 9.0	10.2	29.1	13.1	722	8.4	11/32	2094	31.1	340 A A	CHEVROLET TRAILBLAZER 05
P225/55R17	95H	SL	BSW	265037643	185228	7.0	6.0 - 8.0	9.0	26.8	12.4	784	7.2	10/32	1521	24.5	340 A A	LEXUS LS430 03-04
P245/50ZR17	98W	SL	BSW	265037613	173154	7.5	7.0 - 8.5	10.0	26.7	12.3	786	8.8	10/32	1653	26.5		
215/50R17	91V	SL	BSW	265038963	173153	7.0	6.0 - 7.5	8.9	25.4	11.8	829	8.0	10/32	1356	23.6	360 A A	MAZDA MILLENIA 01-02
P245/45ZR17	95W	SL	BSW	265037604	157722	8.0	7.5 - 9.0	9.8	25.9	11.9	806	8.8	10/32	1521	25.8		
P235/45ZR17	93W	SL	BSW	265037615	157721	8.0	7.5 - 9.0	9.5	25.5	11.8	816	8.5	10/32	1433	23.6		
P275/40ZR17	98W	SL	BSW	265014744	157723	9.5	9.0 - 11.0	10.8	25.7	12.0	805	9.9	10/32	1653	27.7		
<b>SP SPORT 5000 DSST</b>																	
195/55R16	87V	SL	BSW	265021103	183437	6.0	5.5 - 7.0	7.9	24.4	11.3	852	6.5	10/32	1201	23.5	280 A A	MINI COOPER 02-03
245/40ZR18		SL	BSW	265021104	185097	8.0	8.0 - 9.5	9.4	25.6	12.0	816	8.1	10/32	1433	28.6	280 A A	LEXUS SC430 03-04
P245/40R18	93V	SL	BSW	265021140	194912	8.5	8.0 - 9.5	9.8	25.7	12.1	816	8.1	10/32	1433	28.6	340 A A	LEXUS GS460 (option) 05 & LEXUS SC 430 05

UTQG: 340 AA A unless listed otherwise.

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels.



DRIVERS KNOW.®