



SPORT PERFORMANCE

DUNLOP SP SPORT 9000® DSST

**MAXIMUM HIGH-PERFORMANCE
SPORT TIRE WITH DUNLOP
SELF-SUPPORTING
TECHNOLOGY**

FEATURES

- Shoulder block-aligned, high-angle grooves
- HydroMax Technology™ water-shedding tread pattern and powerful, silica-enhanced compound
- Low-angle lateral grooves
- Dunlop Self-Supporting Technology (DSST) featuring patented sidewall construction and specially-developed compounds

BENEFITS

- Enhanced dry surface traction and cornering
- Maximized wet grip, handling and braking
- Maintain high-pressure water flow critical to wet handling
- Continued mobility up to a distance of 50 miles at a maximum speed of 50 mph in normal conditions

SIZE	SERVICE DESC.	LOAD RANGE	SIDE-WALL	PRODUCT CODE	MATERIAL NUMBER	RIM WIDTH (IN)	APPRVD. RIM WIDTHS (IN)	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	STATIC LOADED RADIUS (IN)	REVS/ MILE	TREAD WIDTH (IN)	TREAD DEPTH (IN)	MAX. LOAD (LBS)	TIRE WEIGHT (LBS)	UTQG	OE FITMENT
225/60ZR16	98Z	SL	BSW	265038050	177971	6.5	6.0 - 8.0	9.3	26.7	12.4	783	8.1	10/32	1653	35.3		
225/55ZR16	95Z	SL	BSW	265038077	177972	7.0	6.0 - 8.0	9.5	25.7	12.0	814	8.5	10/32	1521	34.6		
225/50ZR16	92Z	SL	BSW	265038087	177973	7.0	6.0 - 8.0	9.4	24.7	11.6	844	8.1	10/32	1389	29.8		
245/45ZR17	95Z	SL	BSW	265038048	177970	8.0	7.5 - 9.0	10.0	25.7	12.0	811	8.8	10/32	1521	31.5		
235/45ZR17	93Z	SL	BSW	265038096	177974	8.0	7.5 - 9.0	9.7	25.3	11.9	823	8.5	10/32	1433	30.2		
205/45ZR17	84V	SL	BSW	265038021	183793	7.0	6.5 - 7.5	8.1	24.1	11.3	856	7.4	11/32	882	32.4	280 A A	BMW Mini Cooper 02-03

UTQG: 280 AA A unless listed otherwise.

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels.



DRIVERS KNOW.®