

# EXCLAIM™

**A PERFECT COMBINATION OF QUALITY, VALUE AND PERFORMANCE**

The Sawtooth Groove tread pattern allows for excellent all-season traction and performance.

## FEATURES:

- Asymmetrical tread design
- Sawtooth circumferential grooves
- Deep continuous lateral grooves
- Wide circumferential grooves
- Mud and snow rated
- "H" speed rated

## BENEFITS:

- Optimum traction, handling and wear.
- Biting edges for excellent all-season traction.
- Channels water for enhanced wet traction.
- Evacuates water and reduces hydroplaning.
- All-season performance.
- "H" rated for speeds up to 130 mph (209 kph).



UTQG:	TREAD	TRACTION	TEMPERATURE
All Sizes	420	A	A

<b>5</b>	<b>5</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>MILE LIMITED TREADWEAR WARRANTY</b>
88,000 KM					

# XP 2000™ V4

**A RARE BLEND OF HIGH-SPEED PERFORMANCE AND COMFORT**

Biting edges provide excellent all-season traction and performance on this "V" rated tire.

## FEATURES:

- Sawtooth circumferential grooves
- Wide circumferential grooves
- Mud and snow rated
- Full-depth siping
- "V" speed rated

## BENEFITS:

- Biting edges for excellent all-season traction.
- Evacuates water and reduces hydroplaning.
- All-season performance.
- Excellent all-season traction for the life of the tire.
- "V" rated for speeds up to 149 mph (240 kph).



UTQG:	TREAD	TRACTION	TEMPERATURE
All Sizes	320	A	A

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
14	70	P195/70R14	90H	SL	BSW	15472250000	24.7	20.8	9.4	44	7.9 (6.0)	5.0 - 6.5	11/32	834	
	65	P185/65R14	85H	SL	BSW	15472260000	23.5	18.3	8.3	44	7.4 (5.5)	5.0 - 6.5	11/32	877	
		P195/65R14	88H	SL	BSW	15472270000	24.0	19.9	9.0	44	7.9 (6.0)	5.5 - 7.0	11/32	856	
	60	P185/60R14	82H	SL	BSW	15472280000	22.8	17.8	8.1	44	7.4 (5.5)	5.0 - 6.5	11/32	890	
		P195/60R14	85H	SL	BSW	15472290000	23.2	19.1	8.7	44	7.9 (6.0)	5.5 - 7.0	11/32	878	
15	65	P185/65R15	86H	SL	BSW	15472300000	24.5	19.6	8.9	44	7.4 (5.5)	5.0 - 6.5	11/32	849	
		P195/65R15	89H	SL	BSW	15472310000	25.0	19.2	8.7	44	7.9 (6.0)	5.5 - 7.0	11/32	828	
		P205/65R15	92H	SL	BSW	15472320000	25.5	21.6	9.8	44	8.2 (6.0)	5.5 - 7.5	11/32	818	
	60	P215/65R15	95H	SL	BSW	15472330000	26.0	22.9	10.4	44	8.7 (6.5)	6.0 - 7.5	11/32	802	
		P195/60R15	87H	SL	BSW	15472340000	24.2	19.4	8.8	44	7.9 (6.0)	5.5 - 7.0	11/32	850	
		P205/60R15	90H	SL	BSW	15472350000	24.7	20.4	9.3	44	8.2 (6.0)	5.5 - 7.5	11/32	836	
		P215/60R15	93H	SL	BSW	15472360000	25.2	21.8	9.9	44	8.7 (6.5)	6.0 - 7.5	11/32	827	
P225/60R15	95H	SL	BSW	15472370000	25.6	24.8	11.2	44	9.0 (6.5)	6.0 - 8.0	11/32	814			
16	60	P205/60R16	91H	SL	BSW	15472380000	25.7	22.6	10.3	44	8.2 (6.0)	5.5 - 7.5	11/32	811	
		P215/60R16	94H	SL	BSW	15472390000	26.1	23.4	10.6	44	8.7 (6.5)	6.0 - 7.5	11/32	799	
		P225/60R16	97H	SL	BSW	15472400000	26.6	25.8	11.7	44	9.0 (6.5)	6.0 - 8.0	10/32	784	
		P235/60R16	99H	SL	BSW	15472410000	27.1	28.4	12.9	44	9.5 (7.0)	6.5 - 8.5	11/32	769	
	55	P205/55R16	89H	SL	BSW	15472420000	24.9	21.7	9.9	44	8.4 (6.5)	5.5 - 7.5	11/32	831	
		P215/55R16	91H	SL	BSW	15472430000	25.3	23.9	10.9	44	8.9 (7.0)	6.0 - 7.5	11/32	824	
		P225/55R16	94H	SL	BSW	15472440000	25.8	24.3	11.0	44	9.2 (7.0)	6.0 - 8.0	11/32	808	
	50	P205/50R16	86H	SL	BSW	15472450000	24.1	20.8	9.4	44	8.4 (6.5)	5.5 - 7.5	11/32	853	
		P225/50R16	91H	SL	BSW	15472460000	24.9	23.3	10.6	44	9.2 (7.0)	6.0 - 8.0	10/32	831	
P245/50R16	96H	SL	BSW	15472470000	25.7	26.6	12.1	44	10.0 (7.5)	7.0 - 8.5	10/32	811			
17	55	P225/55R17	95H	SL	BSW	15472480000	26.8	26.2	11.9	44	9.2 (7.0)	6.0 - 8.0	11/32	778	
	50	P215/50R17	90H	SL	BSW	15472490000	25.5	23.2	10.5	44	8.9 (7.0)	6.0 - 7.5	11/32	818	
	45	P215/45R17	87H	SL	BSW	15472500000	24.7	21.7	9.8	44	8.4 (7.0)	7.0 - 8.0	11/32	836	
		P245/45R17	95H	SL	BSW	15472510000	25.7	26.0	11.8	44	9.6 (8.0)	7.0 - 9.0	11/32	811	
	40	P205/40R17	80H	SL	BSW	15472520000	23.5	19.9	9.0	44	8.4 (7.5)	7.0 - 8.0	11/32	870	
P215/40R17		83H	SL	BSW	15472530000	23.8	21.0	9.5	44	8.6 (7.5)	7.0 - 8.5	11/32	862		

## XP 2000™ V4

16	60	P225/60R16	98V	SL	BSW	15449770000	26.6	25.4	11.5	44	9.0 (7.5)	7.0 - 9.0	10/32	784
----	----	------------	-----	----	-----	-------------	------	------	------	----	-----------	-----------	-------	-----

PASSENGER PERFORMANCE

BROAD MARKET

SUV / LIGHT TRUCK PERFORMANCE

HIGHWAY

UTILITY

ALL-TERRAIN

EXTREME TRACTION

