



For drivers who want all the luxury and sportiness that their vehicle can offer, Michelin® Pilot® MXM4™ tires are all-season tires designed to elevate the performance characteristics of your luxury touring vehicle. Michelin Pilot MXM4 tires offer our best combination of ride comfort and superb dry, wet and winter traction.

Key Benefits:

- The best ride comfort of our performance touring tires
- Excellent all-season performance and handling
- Advanced tread compounds for long wear and low noise

Tire Specifics:

- All-season tire
- H-, V- and W-speed rated
- Original equipment on vehicles such as:
 - 2005 Audi A6
 - 2005 BMW X3
 - 2005 Jaguar XJ

This tire is available in a ZP version, offering all the same performance characteristics, yet with the peace of mind of Zero Pressure™ Technology. For more information on Zero Pressure Technology, see page 100.



- 1 Long wear and low noise levels promoted by Advanced Technology™ tread compounds.
- 2 Excellent wet traction offered by four deep grooves that channel water away from the tire, helping to combat hydroplaning.
- 3 Ride comfort without sacrificing performance is delivered by Bead Tension Structure.
- 4 Enhanced steering and handling responsiveness due to size-optimized BAZ Technology™ (spiral-wrapped nylon Banded At Zero degrees to tire rotation) that helps control the tire's shape by contributing to resistance of centrifugal forces at high speed.
- 5 All-season traction in wet and winter conditions, thanks to Advanced Technology tread compounds that foster significant adhesion levels in rain and slush.
- 6 Enhanced handling in all winter driving conditions promoted by the auto-blocking effect of the Variable-thickness "zig-zag" sipes.

Performance at a glance:

Tread Life: 9 Wet Traction: 10 Quiet Ride: 9 Handling: 10 Winter Traction: 10 Mud Traction: N/A

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load (lbs@psi)	Original Equipment
P205/55R16	89V	RRBL	70184	5.5 - 7.5	8.3 on 6.5	24.9	10.0	834	1259@51	AC, HO
215/55R16	93H	RRBL	70695	6.0 - 7.5	8.9 on 7.0	25.2	10.0	825	1433@51	AU, V
215/55R16/RF	97H	RRBL	88991	6.0 - 7.5	8.9 on 7.0	25.3	10.0	823	1609@50	VW
225/50R16	92H	RRBL	35385	6.0 - 8.0	9.2 on 7.0	24.9	10.0	836	1389@51	
P225/55R16	94V	RRBL	54929	6.0 - 8.0	9.0 on 7.0	25.75	10.0	811	1477@51	AC
225/55R16	95H	RRBL	70341	6.0 - 8.0	9.3 on 7.0	25.8	10.0	806	1521@51	BM, V
225/60R16	98H	RRBL	18145	6.0 - 8.0	9.0 on 6.5	26.6	10.0	782	1653@51	
225/60R16	98V	RRBL	18839	6.0 - 8.0	9.0 on 6.5	26.6	10.0	782	1653@51	
235/60R16	100H	RRBL	02371	6.5 - 8.5	9.4 on 7.0	27.1	10.0	768	1764@51	
205/50R17/RF	93V	RRBL	89515	5.5 - 7.5	8.4 on 6.5	25.1	10.0	828	1433@50	
215/45R17	87V	RRBL	40315	7.0 - 8.0	8.3 on 7.0	24.6	9.0	845	1201@44	HY
P215/45R17	87V	RRBL	38977	7.0 - 8.0	8.4 on 7.0	24.7	10.0	845	1201@51	AC
215/50R17	91H	RRBL	02122	6.0 - 7.5	8.9 on 7.0	25.5	10.0	815	1356@51	
P215/50R17/XL	93V	RRBL	88482	6.0 - 7.5	8.7 on 7.0	25.5	10.0	819	1433@41	AC, DC, HO
215/55R17	94V	RRBL	12381	6.0 - 7.5	8.9 on 7.0	26.3	10.0	791	1477@51	
225/45R17	90H	RRBL	50248	7.0 - 8.5	8.9 on 7.5	24.8	10.0	844	1323@51	V, VW
225/45R17	91H	RRBL	84377	7.0 - 8.5	8.9 on 7.5	24.8	9.5	838	1356@51	VW
225/45R17/RF	94H	RRBL	59428	7.0 - 8.5	8.9 on 7.5	25.0	10.0	838	1477@50	VW
225/45R17/RF	94H	RRBL	87364	7.0 - 8.5	8.9 on 7.5	25.0	10.0	838	1477@50	
P225/50R17	93V	RRBL	87610	6.0 - 8.0	9.2 on 7.0	25.9	10.0	803	1433@51	HY
225/50R17	94V	RRBL	59993	6.0 - 8.0	9.6 on 7.0	25.9	10.0	803	1477@51	V
P225/55R17	95V	RRBL	79066	6.0 - 8.0	9.2 on 7.0	26.7	10.0	776	1521@35	DC
225/55R17	97H	RRBL	27610	6.0 - 8.0	9.2 on 7.0	26.8	10.0	777	1609@51	
P235/45R17	93W	RRBL	39023	7.5 - 9.0	9.6 on 8.0	25.6	9.0	814	1433@44	AC
235/45R17	94H	RRBL	81652	7.5 - 9.0	9.3 on 8.0	25.4	10.0	820	1477@51	AU
235/45R17	94V	RRBL	21365	7.5 - 9.0	9.3 on 8.0	25.4	10.0	820	1477@51	
235/45R17/RF	97H	RRBL	05103	7.5 - 9.0	9.3 on 8.0	25.4	10.0	820	1609@44	VW
P235/50R17	95V	RRBL	65211	6.5 - 8.5	9.4 on 7.5	26.3	10.0	785	1521@44	F, GM
P235/50R17	95W	RRBL	80928	6.5 - 8.5	9.4 on 7.5	26.3	9.0	796	1521@44	
235/50R17	96H	RRBL	54891	6.5 - 8.5	9.4 on 7.5	26.3	10.0	797	1565@44	J
235/55R17/RF	103H	RRBL	62105	6.5 - 8.5	9.7 on 7.5	27.2	10.0	766	1929@50	VW
235/55R17	98W	RRBL	69362	7.0 - 8.5	9.8 on 7.5	27.0	10.0	769	1653@44	GM
235/55R17	99H	RRBL	49383	6.5 - 8.5	9.7 on 7.5	27.2	10.0	766	1709@51	
235/55R17	99H	RRBL, ZP	84765	7.0 - 8.5	9.8 on 7.5	27.3	10.0	761	1709@51	BM
235/55R17	99H BMW	RRBL	99916	6.5 - 8.5	9.9 on 8.0	27.2	9.5	769	1709@51	BM
245/45R17	95H	RRBL	97946	7.5 - 9.0	9.6 on 8.0	25.7	10.0	810	1521@51	MB
P245/50R17	98V	RRBL	98525	7.0 - 8.5	10.0 on 7.5	26.7	10.0	779	1653@51	AC
P255/45R17	98V	RRBL	85527	8.0 - 9.5	10.0 on 8.5	26.1	10.0	798	1653@44	GM
P225/45R18	91V	RRBL	75447	7.0 - 8.5	8.9 on 7.5	25.9	10.0	802	1356@44	
P235/45R18	94V	RRBL	79598	7.5 - 9.0	9.3 on 8.0	26.5	10.0	790	1478@35	I
235/50R18	97H	RRBL	86861	6.5 - 8.5	9.4 on 7.5	27.5	10.0	759	1609@44	J
235/50R18	97H BMW	RRBL	83609	6.5 - 8.5	9.9 on 8.0	27.2	9.5	768	1609@51	BM
235/50R18	97V BMW	RRBL	96423	6.5 - 8.5	9.7 on 7.5	27.3	10.0	762	1609@51	
P235/50ZR18	97W	RRBL	91426	6.5 - 8.5	9.7 on 7.5	27.3	9.5	761	1609@51	GM
P235/50ZR18	97W	RRBL, ZP	78756	6.5 - 8.5	9.5 on 8.0	27.4	10.0	756	1609@51	GM
P235/60R18	102V	RRBL	94200	6.5 - 9.0	9.5 on 7.0	29.0	10.0	723	1874@44	GM, V
P245/45R18	96V	RRBL	46579	7.5 - 9.0	9.2 on 8.0	26.9	10.0	775	1565@44	I
245/50R18	100V BMW	RRBL	50059	7.0 - 8.5	10.0 on 7.5	27.7	10.0	752	1764@51	
255/45R18/RF	103H	RRBL	92199	8.0 - 9.5	10.0 on 8.5	27.0	10.0	769	1929@50	VW
P255/45ZR18	99W	RRBL	63035	8.0 - 9.5	10.0 on 8.5	27.1	10.0	769	1709@51	GM
P255/55R18	104V	RRBL	51820	7.0 - 9.0	10.4 on 8.0	29.0	10.0	717	1984@44	GM
P235/55R19	101H	RRBL	76158	6.5 - 8.5	9.4 on 7.5	29.1	10.5	717	1819@44	GM

Service Description Key: BMW = BMW
 Original Equipment Key: AC = Acura, AU = Audi, BM = BMW, DC = DaimlerChrysler, F = Ford, GM = General Motors, HO = Honda, HY = Hyundai, I = Infiniti, J = Jaguar, MB = Mercedes-Benz, V = Volvo, VW = Volkswagen
 RF = European designation for XL (Extra Load)

- The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
- Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires, and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.
DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tire and Rim Technical Organization Standards Manual.

For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

H-Speed Rated Sizes:		100	106	112	118	124	130			
Maximum Speed (mph)		100	106	112	118	124	130			
Inflation Increase (psi)		0.0	1.0	2.0	3.0	4.0	5.0			
Load Capacity (% of max.)		100	100	100	100	100	100			
V-Speed Rated Sizes:		100	106	112	118	124	130	136	143	149
Maximum Speed (mph)		100	106	112	118	124	130	136	143	149
Inflation Increase (psi)		0	1	2	3	4	5	5	5	5
Load Capacity (% of max.)		100	100	100	100	100	100	97	94	91
W-Speed Rated Sizes:		118	124	130	136	143	149	155	161	168
Maximum Speed (mph)		118	124	130	136	143	149	155	161	168
Inflation Increase (psi)		0	1.5	3.0	4.5	6.0	7.5	7.5	7.5	7.5
Load Capacity (% of max.)		100	100	100	100	100	100	95	90	85

UTQG Rating

Treadwear 300
 Traction A
 Temperature A

