



Michelin® Pilot® XGT® H4 tires provide an exceptionally high level of performance characteristics in an H-performance-rated all-season tire. Michelin Pilot XGT H4 tires are designed for drivers looking for tight, responsive handling in nearly any weather conditions, all while offering long, even treadwear and a smooth, quiet ride.

Key Benefits:

- Confident wet-weather performance
- Exceptional comfort in a high performance tire
- Long tread life
- Excellent street handling

Tire Specifics:

- All-season tire
- H-speed rated



- 1 Powerful wet traction, excellent snow traction and progressive handling result from the Advanced Technology™ all-season tread.
- 2 Powerful, progressive, driver-friendly cornering because of a high-strength belt package.
- 3 Helps combat hydroplaning and maximizes wet traction with progressively angled, variable-width lateral grooves and wide, see-through circumferential grooves.
- 4 Positive snow traction due to deep sipes and tread-block rigidity.
- 5 Exceptional treadwear because of dynamically stress-balanced casing.
- 6 Optimized performance promoted by exclusive BAZ Technology™ (spiral-wrapped nylon Banded At Zero degrees to tire rotation), which helps ensure casing integrity and tire shape during high performance driving.

Performance at a glance:

Tread Life: 10 Wet Traction: 7 Quiet Ride: 10 Handling: 7 Winter Traction: 7 Mud Traction: N/A

NOTE: These comparisons are among Michelin Ultra-High Performance tires.
© 2005 Michelin North America, Inc. All rights reserved.
MDL40680

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load (lbs@psi)
P185/60R14	82H	RRBL	55415	5.0 - 6.5	7.5 on 5.5	22.9	10.0	911	1047@44
P195/60R14	85H	RRBL	60679	5.5 - 7.0	7.8 on 6.0	23.3	10.0	893	1135@44
P205/60R14	88H	RRBL	72496	5.5 - 7.5	8.3 on 6.0	24.0	10.0	868	1235@44
P215/60R14	91H	RRBL	53484	6.0 - 7.5	8.5 on 6.5	24.0	10.0	867	1345@44
P225/60R14	94H	RRBL	44213	6.0 - 8.0	9.0 on 6.5	24.9	10.0	837	1455@44
P195/50R15	81H	RRBL	79251	5.5 - 7.0	7.9 on 6.0	22.8	10.0	911	1019@44
P195/60R15	87H	RRBL	43374	5.5 - 7.0	7.8 on 6.0	24.4	10.0	854	1190@44
P195/65R15	89H	RRBL	78035	5.5 - 7.0	8.0 on 6.0	25.2	10.0	826	1279@44
P205/50R15	84H	RRBL	53256	5.5 - 7.5	8.4 on 6.5	23.2	10.0	894	1113@44
P205/60R15	90H	RRBL	60870	5.5 - 7.5	8.3 on 6.0	25.0	10.0	833	1301@44
P205/65R15	92H	RRBL	98009	5.5 - 7.5	8.1 on 6.0	25.2	10.0	827	1400@44
P215/60R15	93H	RRBL	46536	6.0 - 7.5	8.5 on 6.5	25.0	10.0	832	1411@44
P215/65R15	95H	RRBL	50560	6.0 - 7.5	8.7 on 6.5	26.4	10.0	790	1510@44
P225/60R15	95H	RRBL	64314	6.0 - 8.0	9.1 on 6.5	25.9	10.0	802	1521@44
P225/70R15	100H	RRBL	91868	6.0 - 7.5	8.9 on 6.5	27.3	10.0	764	1753@44
P235/60R15	98H	RRBL	82086	6.5 - 8.5	9.3 on 7.0	26.0	10.0	801	1642@44
P205/55R16	89H	RRBL	89877	5.5 - 7.5	8.3 on 6.5	25.1	10.0	827	1279@44
P215/60R16	94H	RRBL	74511	6.0 - 7.5	8.7 on 6.5	26.3	10.0	791	1477@44
P225/50R16	91H	RRBL	98227	6.0 - 8.0	8.9 on 7.0	24.9	10.0	834	1367@44
P225/55R16	94H	RRBL	91592	6.0 - 8.0	8.9 on 7.0	25.7	10.0	812	1477@44
P225/60R16	97H	RRBL	61689	6.0 - 8.0	9.0 on 6.5	26.9	10.0	772	1609@44
P235/60R16	99H	RRBL	41330	6.5 - 8.5	9.3 on 7.0	27.0	10.0	770	1709@44
P245/50R16	96H	RRBL	46892	7.0 - 8.5	10.0 on 8.5	25.9	10.0	806	1576@44
P255/50R16	99H	RRBL	63596	7.0 - 9.0	10.2 on 8.0	25.9	10.0	806	1687@44
205/40R17	80H	RRBL	50923	7.0 - 8.0	8.3 on 7.5	23.5	10.0	881	992@44
215/40R17	83H	RRBL	71740	7.0 - 8.5	8.5 on 7.5	23.9	10.0	866	1074@44
215/45R17	87H	RRBL	88958	7.0 - 8.0	8.3 on 7.0	24.8	10.0	836	1201@44
215/50R17	91H	RRBL	84984	6.0 - 7.5	8.9 on 7.0	25.6	10.0	808	1356@44
225/45R17	90H	RRBL	49113	7.0 - 8.5	8.7 on 7.5	25.2	10.0	823	1323@44
235/45R17	93H	RRBL	80907	7.5 - 9.0	9.4 on 8.0	25.6	10.0	810	1433@44
245/45R17	95H	RRBL	45940	8.0 - 9.5	9.5 on 8.0	25.7	10.0	814	1521@44
225/40R18	88H	RRBL	84919	7.5 - 9.0	9.0 on 8.0	25.3	10.0	819	1235@44

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
 2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires, and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.
DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

H-Speed Rated Sizes:	100	106	112	118	124	130
Maximum Speed (mph)	0.0	1.0	2.0	3.0	4.0	5.0
Inflation Increase (psi)	100	100	100	100	100	100
Load Capacity (% of max.)	100	100	100	100	100	100

UTQG Rating

Treadwear 400
 Traction A
 Temperature A

