

TOYO TIRES®

PROXES RA1™ D.O.T. APPROVED COMPETITION RADIAL



The performance-proven RA1™ features all the high-tech components to provide an uncommon advantage to the cost-conscious competitor who still demands quick lap time. It's true performance from Toyo!

Typical Vehicle Matches

Race prepared vehicles.

Typical Customer Matches

Improved touring, club, and endurance racers.

Competitive Products

- Hoosier R3S04
- Kumho Victoracer V700, Ecsta V700
- Michelin Pilot Sport Cup
- Pirelli PZero Corsa
- Yokohama A032R, A048

UTQG
100 AA A



Official Spec
Tire of
SPEED
World Challenge



Customer Benefit	Product Features
Competitive Handling	<ul style="list-style-type: none"> • Soft, but durable tread compound • Advanced race-proven casing design • Two steel belts • Spiral wound cap ply (construction may vary by size) • Steel wire reinforced sidewalls (construction may vary by size)
Steering Response	<ul style="list-style-type: none"> • Heavy-duty bead construction • Steel belted construction • Steel wire reinforced sidewalls (construction may vary by size)
Wet and Dry Traction	<ul style="list-style-type: none"> • Stepped tread design • Tread depth can be shaved to maximize dry traction response • Full tread depth of 8/32nds provides aggressive wet traction
Treadlife	<ul style="list-style-type: none"> • Steel belted construction

Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (32")	Inflated Dimension		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Price
					Overall Diameter (inch)	Overall Width (inch)					
185/60R13 80V	236680	5.0-5.5-6.5	18	8	21.7	7.4	10.0	992	44	1010	
205/60R13 86V	236700	5.5-6.0-7.5	20	8	22.7	8.2	10.4	1158	44	970	
205/55R14 85V	236870	5.5-6.5-7.5	21	8	22.9	8.4	10.0	1135	44	955	
225/50R14 89V	236900	6.0-7.0-8.0	23	8	22.9	8.9	10.5	1279	44	955	
205/50ZR15	236840	5.5-6.5-7.5	20	8	23.1	8.4	10.6	1135	44	917	
225/50ZR15	236830	6.0-7.0-8.0	23	8	23.9	9.2	10.9	1323	44	886	
225/45ZR15		7.0-7.5-8.5	23	8	22.9	9.0	10.6	1201	44	908	
205/55ZR16	236850	5.5-6.5-7.5	23	8	24.9	8.4	11.4	1235	44	853	
225/50ZR16	236890	6.0-7.0-8.0	23	8	24.9	9.2	11.2	1390	44	853	
P255/50ZR16	236880	7.0-8.0-9.0	27	8	26.1	10.4	11.7	1687	44	815	
245/45ZR16	236800	7.5-8.0-9.0	25	8	24.7	9.6	11.2	1477	44	861	
205/50ZR17	236740	5.5-6.5-7.5	24	8	25.2	8.3	11.7	1279	44	823	
235/45ZR17	236820	7.5-8.0-9.0	25	8	25.4	9.3	11.6	1488	44	834	
205/40ZR17 RD	236750	7.0-7.5-8.0	19	8	23.5	8.4	11.0	1102	50	887	
235/40ZR17	236760	8.0-8.5-9.5	24	8	24.4	9.6	11.4	1323	44	852	
255/40ZR17	236770	8.5-9.0-10.0	26	8	25.0	10.4	11.7	1477	44	828	
275/40ZR17	236780	9.0-9.5-11.0	29	8	25.7	10.9	10.0	1653	44	812	
225/40ZR18 RD	236790	7.5-8.0-9.0	23	8	25.1	9.1	9.8	1389	50	827	
245/40ZR18	236690	8.0-8.5-9.5	25	8	25.6	9.7	12.0	1433	44	812	
275/35ZR18	236710	9.0-9.5-11.0	30	8	25.6	10.9	12.0	1521	44	812	
305/35ZR18	236730	10.0-11.0-12.0	32	8	26.3	12.5	12.2	1819	44	790	
335/30ZR18	236720	11.5-12.0-13.0	34	8	25.9	13.5	12.1	1874	44	803	

RD = Reinforced. Bold designates measuring rim width. When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph. All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.

PERFORMANCE