

PROXES S/T™ HIGH-PERFORMANCE SPORT TRUCK AND SUV RADIAL



The Proxes S/T is a high-performance tire that delivers a powerful combination of superb handling, confident all-season performance and a smooth, stable ride. The H, V, W and Y speed-rated Proxes S/T offers plus-sizing opportunities on pickup trucks, sport utility vehicles and Original Equipment fitments on high performance crossover SUVs.

Typical Vehicle Matches

Chevrolet Tahoe, Suburban, C/K pickups; Dodge Durango, Ram; Ford Expedition, F-150 pickups; GMC Yukon, Jimmy, Sierra; Infiniti QX4; Jeep Grand Cherokee; Lexus LX 470; Mercedes-Benz ML320, ML430; Nissan Pathfinder. OE fitments for: VW Toureg, Nissan Murano, FX45; BMW X5; Land Rover.

Typical Customer Matches

Performance and style-conscious enthusiasts; vehicle-oriented owners of sport trucks and sport-utility vehicles; upgraders from Original Equipment tires.

Competitive Products

- Dunlop Rover GTX
- Pirelli Scorpion Zero
- Yokohama AVS S/T



| Customer Benefit | Product Features |
|--------------------------|---|
| Wet and Dry Handling | <ul style="list-style-type: none"> • Computer-optimized, unidirectional all-season tread design • Angled tread grooves • Cap/base tread compound • H, V, W and Y speed-rated |
| Steering Response | <ul style="list-style-type: none"> • Specially engineered polyester casing • High-ply turn-up construction • High bead filler • Two wide high-tensile steel belts |
| All-Season Performance | <ul style="list-style-type: none"> • Computer-optimized, unidirectional all-season tread design • Double V-shaped tread grooves • Cap/base tread compound • M&S rated |
| Quiet, Stable Ride | <ul style="list-style-type: none"> • Computer-optimized, unidirectional all-season tread design • Jointless bead wire • Jointless two-cap ply (construction may vary size by size) • Two wide, high-tensile steel belts |
| Durability and Long Life | <ul style="list-style-type: none"> • Jointless bead wire • Two wide, high-tensile steel belts • Cap/base tread compound • Rim protector • 420 UTQG Treadwear rating |
| Sporty Appearance | <ul style="list-style-type: none"> • Wide, low-profile design • Ultra-modern sidewall styling • Aggressive, unidirectional all-season tread design |

**500 MILE
or 45 DAY
TRIAL OFFER
AVAILABLE**
LIMITED WARRANTY.
ASK FOR DETAILS.



PROXES S/T™ HIGH-PERFORMANCE SPORT TRUCK AND SUV RADIAL

UTQG
420 A A



| Tire Size | Product Code | Approved Rim Width Range (inch) | Tire Weight (lbs.) | Tread Depth (32") | Inflated Dimension | | Static Loaded Radius (inch) | Max. Load (lbs.) | Max. Pressure (PSI) | Revs Per Mile | Price |
|--------------------|--------------|---------------------------------|--------------------|-------------------|-------------------------|----------------------|-----------------------------|------------------|---------------------|---------------|-------|
| | | | | | Overall Diameter (inch) | Overall Width (inch) | | | | | |
| P275/60R15 107H | 242100 | 7.5-8.0-9.5 | 30 | 11 | 28.0 | 11.0 | 12.5 | 2149 | 44 | 744 | |
| P295/50R15 105H | 242120 | 8.0-9.5-10.0 | 34 | 12 | 26.7 | 12.2 | 12.0 | 2061 | 44 | 783 | |
| 245/70R16 107V | 242660 | 6.5-7.0-8.0 | 34 | 11 | 29.6 | 9.7 | 13.3 | 2149 | 44 | 702 | |
| 265/70R16 112V | 242670 | 7.0-8.0-9.0 | 39 | 11 | 30.7 | 10.3 | 13.7 | 2469 | 44 | 676 | |
| 275/70R16 114H | 242190 | 7.0-8.0-9.0 | 38 | 11 | 31.2 | 11.0 | 14.0 | 2601 | 44 | 664 | |
| 275/60R16 109V | 242180 | 7.5-8.0-9.5 | 40 | 11 | 29.0 | 11.0 | 13.0 | 2271 | 44 | 720 | |
| 235/65R17 104V | 242640 | 6.5-7.5-8.5 | 31 | 11 | 28.9 | 9.5 | 13.2 | 1984 | 44 | 718 | |
| 255/60R17 110V RD | 242240 | 7.0-7.5-9.0 | 37 | 11 | 29.1 | 10.2 | 13.2 | 2337 | 50 | 717 | |
| 275/60R17 111V | 242220 | 7.5-8.0-9.5 | 39 | 11 | 30.0 | 11.0 | 13.5 | 2403 | 44 | 694 | |
| 285/60R17 114V | 242230 | 8.0-8.5-10.0 | 42 | 11 | 30.5 | 11.5 | 13.7 | 2601 | 44 | 683 | |
| 225/55R17 97V | 242630 | 6.0-7.0-8.0 | 27 | 11 | 26.7 | 9.1 | 12.3 | 1609 | 44 | 777 | |
| 275/55R17 109V | 242620 | 7.5-8.5-9.5 | 38 | 11 | 28.9 | 11.1 | 13.1 | 2271 | 44 | 720 | |
| 255/60R18 112V RD | 242650 | 7.0-8.0-9.0 | 37 | 11 | 30.0 | 10.4 | 13.7 | 2469 | 50 | 693 | |
| 285/60R18 116V | 242270 | 8.0-8.5-10.0 | 43 | 11 | 31.5 | 11.5 | 14.3 | 2756 | 44 | 661 | |
| 305/60R18 120V | 242290 | 8.5-9.0-11.0 | 47 | 12 | 32.4 | 12.0 | 12.6 | 3086 | 44 | 645 | |
| 255/55R18 109V RD | 242160 | 7.0-8.0-9.0 | 34 | 11 | 29.0 | 10.4 | 13.3 | 2271 | 50 | 718 | |
| 275/55R18 114V RD | 242480 | 7.5-8.5-9.5 | 39 | 11 | 29.8 | 11.1 | 13.6 | 2601 | 50 | 696 | |
| 255/50R18 106V RD | 242470 | 7.0-8.0-9.0 | 34 | 11 | 27.9 | 10.2 | 12.9 | 2094 | 50 | 744 | |
| 285/50R18 109V | 242610 | 8.0-9.0-10.0 | 37 | 11 | 29.1 | 10.4 | 13.3 | 2271 | 44 | 715 | |
| 255/45R18 99V | 242590 | 8.0-8.5-9.5 | 30 | 11 | 27.1 | 10.0 | 12.5 | 1709 | 44 | 767 | |
| 295/45R18 108V | 242280 | 9.5-10.0-11.0 | 39 | 11 | 28.5 | 11.7 | 13.0 | 2205 | 44 | 733 | |
| 255/50R19 103V | 242600 | 7.0-8.0-9.0 | 36 | 11 | 29.1 | 10.4 | 13.4 | 1929 | 44 | 714 | |
| 275/45R19 108Y RD* | 242580 | 8.5-9.0-10.5 | 34 | 10 | 28.8 | 10.8 | 13.3 | 2205 | 50 | 722 | |
| 285/45R19 107V | 242570 | 9.0-9.5-10.5 | 35 | 11 | 29.1 | 11.2 | 13.4 | 2149 | 44 | 714 | |
| 255/50R20 109V RD | 242490 | 7.0-8.0-9.0 | 31 | 11 | 29.9 | 10.2 | 13.9 | 2271 | 50 | 694 | |
| 265/50R20 112V RD | 242300 | 7.5-8.5-9.5 | 42 | 11 | 30.5 | 10.5 | 14.1 | 2469 | 50 | 683 | |
| 285/50R20 116V RD | 242710 | 8.0-9.0-10.0 | 42 | 11 | 31.1 | 11.6 | 14.3 | 2756 | 50 | 669 | |
| 305/50R20 120V RD | 242350 | 8.5-9.5-11.0 | 45 | 12 | 32.1 | 12.4 | 14.6 | 3086 | 50 | 651 | |
| 325/50R20 120V | 242340 | 9.0-10.0-11.5 | 49 | 12 | 32.8 | 13.2 | 12.7 | 3086 | 44 | 636 | |
| 255/45R20 105V RD | 242450 | 8.0-8.5-9.5 | 33 | 11 | 29.1 | 10.4 | 13.5 | 2039 | 50 | 714 | |
| 265/45R20 108V RD | 242560 | 8.5-9.0-10.0 | 34 | 11 | 29.4 | 10.5 | 13.7 | 2205 | 50 | 707 | |
| 295/45R20 114V RD | 242320 | 9.5-10.0-11.0 | 40 | 11 | 30.5 | 11.7 | 14.1 | 2601 | 50 | 683 | |
| 255/40R20 101V RD | | 8.5-9.0-10.0 | 30 | 10 | 28.0 | 10.1 | 13.1 | 1819 | 50 | 743 | |
| 275/40R20 102W | 242550 | 9.0-9.5-11.0 | 34 | 11 | 28.6 | 10.9 | 13.3 | 1874 | 44 | 727 | |
| 295/40R20 106V | 242510 | 10-10.5-11.5 | 36 | 11 | 29.2 | 11.7 | 13.6 | 2094 | 44 | 711 | |
| 315/35R20 106W | 242540 | 10.5-11.0-12.5 | 35 | 11 | 28.6 | 12.3 | 13.3 | 2094 | 44 | 727 | |
| 325/50R22 120V | 242680 | 9.0-10.0-11.5 | 61 | 11 | 34.7 | 13.0 | 15.9 | 3086 | 44 | 599 | |
| 285/45R22 114V | | 9.0-9.5-10.5 | 42 | 11 | 32.2 | 11.2 | 15.0 | 3086 | 44 | 645 | |
| 305/45R22 118V RD | 242370 | 9.5-10.0-11.5 | 48 | 11 | 32.8 | 12.0 | 15.2 | 2910 | 50 | 636 | |
| 265/40R22 106V RD | 242460 | 9.0-9.5-10.5 | 45 | 11 | 30.4 | 10.7 | 14.3 | 2094 | 50 | 684 | |
| 305/40R22 114V RD | 242390 | 10.0-10.5-12.0 | 45 | 11 | 31.6 | 12.3 | 14.7 | 2601 | 50 | 657 | |
| 325/40R22 118V RD | 242360 | 11.0-11.5-13.0 | 49 | 11 | 32.2 | 12.8 | 15.0 | 2910 | 50 | 644 | |
| 285/35R22 102W | 242530 | 9.5-10.0-11.0 | 39 | 11 | 29.9 | 11.3 | 14.1 | 1874 | 44 | 694 | |
| 295/30R22 103Y RD* | 242520 | 10.0-10.5-11.0 | 36 | 10 | 29.1 | 11.5 | 13.8 | 1929 | 50 | 715 | |
| 305/40R23 115V RD | 242380 | 10.0-11.0-12.0 | 45 | 11 | 32.6 | 12.0 | 15.3 | 2679 | 50 | 636 | |
| 285/35R23 107V RD | 242500 | 9.5-10.0-11.0 | 40 | 11 | 30.9 | 11.3 | 14.6 | 2149 | 50 | 671 | |
| 325/45R24 120V RD | | 10.0-11.0-12.0 | 54 | 11 | 35.4 | 12.6 | 16.4 | 2601 | 50 | 588 | |
| 285/40R24 112V RD | | 9.5-10.0-11 | 46 | 11 | 32.9 | 11.3 | 15.5 | 2469 | 50 | 631 | |

RD = Reinforced. Rim protector on all sizes. Bold designates measuring rim width. When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph. All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.
* UTQG rating is 280 A A, summer tires only, not M&S rated.