

TOYO TIRES®

PERFORMANCE

PROXES TPT™ TOTAL PERFORMANCE TOURING TIRE

The all-season Proxes TPT is the ideal performance touring replacement for modern cars equipped with T, H or V speed-rated tires as Original Equipment. Optimized casing design and a unique directional tread combine to provide superior wet or dry grip and handling with excellent ride comfort and long treadlife.

Typical Vehicle Matches

Acura 3.2 TL; Audi; BMW; Cadillac STS; Chrysler Sebring; Honda Accord; Infiniti; Lexus ES, LS, SC, GS; Mazda 6; Mercedes-Benz; Nissan Altima, Maxima; Pontiac Bonneville; Grand Prix GTP; Toyota Avalon, Camry; Volkswagen Jetta, Passat; Volvo.

Typical Customer Matches

Discriminating style-conscious buyers upgrading from Original Equipment touring tires.

Competitive Products

- BFGoodrich Traction T/A
- Bridgestone Turanza LS
- Continental ContiPremierContact
- Dunlop SP Sport A2
- Goodyear Eagle RS-A
- Michelin Energy MXV4, Pilot XG-T H4/V4
- Pirelli P6000 Sport Veloce, P6 Four Seasons
- Yokohama Avid H4s/V4s



Customer Benefit	Product Features
Handling	<ul style="list-style-type: none"> • High-modulus bead filler • Jointless, spiral-wound nylon cap and edge ply (construction may vary by size) • T-Mode™ Design Technology • Center rib designed for straight line stability • T, H and V speed-rated
Wet Traction	<ul style="list-style-type: none"> • Well-balanced sipes for wet traction • Unidirectional tread for improved aquaplaning resistance
All-Season Traction	<ul style="list-style-type: none"> • Unidirectional, touring-performance, all-season tread design • Aggressive siping • Optimized tread groove shape and angle • M&S rated
Smooth, Comfortable Ride	<ul style="list-style-type: none"> • T-Mode Design Technology • Strong polyester casing • Low-noise tread design • Jointless, spiral-wound nylon cap and edge ply (construction may vary by size)
Style	<ul style="list-style-type: none"> • High-image sidewall styling with embossed, stylized lettering • Unidirectional tread design
Long Treadlife	<ul style="list-style-type: none"> • Two full-width steel belts • Cap/base tread compound • 65,000-mile treadwear limited warranty • 400 UTQG Treadwear rating

65,000 MILE
TREADWEAR LIMITED WARRANTY
ASK FOR DETAILS



500 MILE or 45 DAY TRIAL OFFER AVAILABLE
LIMITED WARRANTY. ASK FOR DETAILS.

PROXES TPT™ TOTAL PERFORMANCE TOURING TIRE

UTQG
400 A A



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (3/32")	Inflated Dimension		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Price
					Overall Diameter (inch)	Overall Width (inch)					
P195/70R14 90H	187680	5.0-6.0-6.5	19	11	24.8	7.9	11.2	1312	44	838	
185/65R14 86H											
P185/60R14 82H	187500	5.0-5.5-6.5	16	10	22.8	7.4	10.4	1047	44	918	
P195/60R14 85H	187510	5.5-6.0-7.0	17	10	23.2	7.9	10.6	1135	44	899	
185/65R15 88H	187620	5.0-5.5-6.5	17	10	24.5	7.4	11.1	1235	44	855	
195/65R15 91H	187630	5.5-6.0-7.0	19	10	25.0	7.9	11.3	1356	44	836	
195/65R15 91V	187780	5.5-6.0-7.0	19	10	25.0	7.9	11.3	1356	44	836	
205/65R15 94H	187640	5.5-6.0-7.5	19	10	25.5	8.2	11.5	1477	44	822	
205/65R15 94V	187660	5.5-6.0-7.5	20	10	25.5	8.2	11.5	1477	44	822	
P215/65R15 95H	187670	6.0-6.5-7.5	21	10	26.0	8.7	11.7	1510	44	803	
195/60R15 88H	187520	5.5-6.0-7.0	18	10	24.2	7.9	11.0	1235	44	862	
195/60R15 88V	187800	5.5-6.0-7.0	18	10	24.2	7.9	11.0	1235	44	862	
205/60R15 91H	187530	5.5-6.0-7.5	20	10	24.7	8.2	11.2	1356	44	847	
205/60R15 91V	187540	5.5-6.0-7.5	21	10	24.7	8.2	11.2	1356	44	847	
P215/60R15 93H	187550	6.0-6.5-7.5	21	11	25.2	8.7	11.4	1433	44	830	
225/60R15 96H	187560	6.0-6.5-8.0	23	11	25.6	9.0	11.6	1565	44	814	
225/60R15 96V	187570	6.0-6.5-8.0	23	11	25.6	9.0	11.6	1565	44	814	
195/55R15 85V	187410	5.5-6.0-7.0	18	10	23.4	7.9	10.7	1135	44	890	
205/65R16 95H	187700	5.5-6.0-7.5	22	10	26.5	8.2	12.0	1521	44	789	
P205/60R16 91V	187580	5.5-6.0-7.5	21	10	25.7	8.2	11.7	1356	44	813	
215/60R16 95V	187690	6.0-6.5-7.5	23	11	26.1	8.7	11.9	1521	44	797	
225/60R16 98H	187590	6.0-6.5-8.0	25	11	26.6	9.0	12.1	1653	44	784	
225/60R16 98V	187600	6.0-6.5-8.0	25	11	26.6	9.0	12.1	1653	44	784	
235/60R16 100H	187610	6.5-7.0-8.5	26	11	27.1	9.5	12.3	1764	44	766	
205/55R16 94H RD	187450	5.5-6.5-7.5	21	10	24.9	8.4	11.4	1477	50	839	
205/55R16 94V RD	187460	5.5-6.5-7.5	21	10	24.9	8.4	11.4	1477	50	839	
215/55R16 93H	187470	6.0-7.0-7.5	21	10	25.3	8.9	11.6	1433	44	826	
215/55R16 93V	187810	6.0-7.0-7.5	21	10	25.3	8.9	11.6	1433	44	826	
225/55R16 95H	187480	6.0-7.0-8.0	24	10	25.8	9.2	11.8	1521	36	811	
225/55R16 95V	187490	6.0-7.0-8.0	25	10	25.8	9.2	11.8	1521	36	811	
195/50R16 84V	187310	5.5-6.0-7.0	19	10	23.7	7.9	10.9	1102	44	881	
205/50R16 87V	187710	5.5-6.5-7.5	21	10	24.1	8.3	11.2	1202	44	861	
215/50R16 90V											
225/50R16 92V	187720	6.0-7.0-8.0	23	10	24.7	9.1	11.4	1389	44	840	
215/55R17 94V	187760	6.0-7.0-7.5	24	10	26.2	8.8	12.1	1477	44	793	
215/55R17 94H	187770	6.0-7.0-7.5	24	10	26.2	8.8	12.1	1477	44	793	
225/55R17 97V	187420	6.0-7.0-8.0	27	10	26.8	9.2	12.3	1609	44	776	
225/55R17 97T	187430	6.0-7.0-8.0	27	10	26.8	9.2	12.3	1609	44	776	
235/55R17 99H	187830	6.5-7.5-8.5	28	10	27.1	9.5	12.4	1709	44	768	
235/55R17 99V	187790	6.5-7.5-8.5	28	10	27.1	9.5	12.4	1709	44	768	
215/50R17 95V RD	187370	6.0-7.0-7.5	26	10	25.5	8.9	11.9	1521	50	813	
225/50R17 94V	187740	6.0-7.0-8.0	26	10	25.8	9.1	11.9	1477	44	806	
235/50R17 96V	187750	6.5-7.5-8.5	26	10	26.3	9.7	12.1	1565	44	790	

RD = Reinforced. Rim protector on 55 and lower aspect ratios. Bold designates measuring rim width. When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph. All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.