

## PROXES T1-S™ ULTRA-HIGH PERFORMANCE RADIAL

*The Proxes T1-S is the new generation of ultra-high performance tire for the world's most demanding cars and discriminating drivers. The smooth-riding V, W and Y speed-rated T1-S offers excellent dry and wet grip, exceptional handling and resistance to aquaplaning.*

### Typical Vehicle Matches


Acura NSX; Audi S4; BMW 3 Series, 5 Series;  
Cadillac CTS-V; Chevrolet Corvette; Ford Mustang GT;  
Honda S2000; Infiniti G35; Lexus IS 300, GS300/430;  
Mazda RX-8; Mercedes-Benz C Class, E Class;  
Mitsubishi Lancer Evolution VIII; Nissan 350Z;  
Pontiac GTO; Porsche 911, Subaru WRX.

### Typical Customer Matches

True performance enthusiasts.

### Competitive Products

- BFGoodrich g-Force T/A KDW
- Bridgestone Potenza S02/S03
- Continental ContiSportContact 2
- Dunlop SP Sport 9000
- Goodyear Eagle F1 GS-D3
- Michelin Pilot Sport-2
- Pirelli PZero System
- Yokohama AVS Sport



Customer Benefit	Product Features
Wet and Dry Grip	<ul style="list-style-type: none"> <li>• “Generation S” silica-reinforced, high-grip tread compound</li> <li>• Small void ratio tread design with long stiff slanted ribs</li> <li>• Unique, wide-open radial tread grooves for highly effective water evacuation</li> </ul>
Steering Response	<ul style="list-style-type: none"> <li>• DSOC II™ Technology</li> <li>• Wide stable shoulder blocks</li> <li>• Hard bead filler compound</li> <li>• Reduced side-ply cord angle increases bead stiffness</li> <li>• High-modulus casing (rayon or polyester depending on size)</li> <li>• Ultra-high performance tread design</li> </ul>
Wet Traction and Dry Performance	<ul style="list-style-type: none"> <li>• “Generation S” silica-reinforced, high-grip tread compound</li> <li>• Unidirectional tread pattern with slanted main grooves</li> <li>• Rigid center tread rib</li> </ul>
High-Speed Stability	<ul style="list-style-type: none"> <li>• Solid center tread rib</li> <li>• DSOC II Technology</li> <li>• Spiral-wound, jointless edge and cap plies (construction may vary by size)</li> <li>• Jointless bead wire</li> <li>• High-modulus casing (rayon or polyester depending on size)</li> <li>• Two full-width steel belts</li> </ul>
Smooth, Comfortable Quiet Ride	<ul style="list-style-type: none"> <li>• DSOC II Technology</li> <li>• Jointless bead wire</li> <li>• Spiral-wound, jointless edge and cap plies (construction may vary by size)</li> <li>• Variable-pitch block tread pattern</li> </ul>
Appearance	<ul style="list-style-type: none"> <li>• Unique unidirectional tread pattern</li> <li>• Optimized, low-profile design</li> <li>• Sleek sidewall styling</li> </ul>
Durability and Long Life	<ul style="list-style-type: none"> <li>• DSOC II Technology</li> <li>• “Generation S” silica-reinforced, high-grip tread compound</li> <li>• Rim protector protects rim flange</li> </ul>

# TOYO TIRES®

PERFORMANCE



## PROXES T1-S™ ULTRA-HIGH PERFORMANCE RADIAL

**UTQG**  
All sizes  
280 AA A



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (32")	Inflated Dimension		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Price
					Overall Diameter (inch)	Overall Width (inch)					
195/55R14 82V	250200	5.5-6.0-7.0	17	10	22.4	7.9	10.5	1047	44	924	
195/45R14 77V	241800	6.0-6.5-7.5	15	10	20.9	7.7	9.7	908	44	990	
185/55R15 82V	242020	5.0-6.0-6.5	16	10	23.0	7.6	10.6	1047	44	900	
195/55R15 85V	242030	5.5-6.0-7.0	17	10	23.4	7.9	10.8	1135	44	885	
205/55R15 88V	242040	5.5-6.5-7.5	18	10	23.9	8.4	11.0	1235	44	868	
195/50R15 82V	241930	5.5-6.0-7.0	17	10	22.7	7.9	10.5	1047	44	914	
205/50R15 89V RD	241940	5.5-6.5-7.5	19	10	23.1	8.4	10.7	1278	50	899	
225/50R15 91V	241950	6.0-7.0-8.0	20	10	23.9	9.2	11.0	1356	44	868	
195/45R15 78V	241810	6.0-6.5-7.5	16	10	21.9	7.7	10.2	937	44	946	
215/45R15 88V RD	241820	7.0-8.0	18	10	22.6	8.4	10.5	1234	50	913	
205/55ZR16 91W	242050	5.5-6.5-7.5	21	10	24.9	8.4	11.4	1356	44	836	
215/55ZR16 93W	242060	6.0-7.0-7.5	22	10	25.3	8.9	11.7	1433	44	816	
225/55ZR16 96W	242070	6.0-7.0-8.0	24	10	25.8	9.2	11.8	1565	44	807	
245/55ZR16 100W	242080	7.0-7.5-8.5	27	10	26.6	10.0	12.1	1764	44	781	
185/50R16 81V	241780	5.0-6.0-6.5	18	10	23.3	7.6	10.9	1019	44	890	
195/50R16 84V	241790	5.5-6.0-7.0	19	10	23.7	7.9	11.0	1102	44	876	
205/50ZR16 87W	241960	5.5-6.5-7.5	19	10	24.1	8.4	11.2	1201	44	861	
225/50ZR16 92W	241970	6.0-7.0-8.0	23	10	24.9	9.2	11.4	1389	44	836	
235/50ZR16 95W	241980	6.5-7.5-8.5	24	10	25.3	9.7	11.6	1521	44	821	
195/45ZR16 80V	250350	6.0-6.5-7.5	17	10	22.9	7.7	10.7	992	44	900	
205/45ZR16 87W RD	241830	6.5-7.0-7.5	18	10	23.2	8.1	10.8	1201	50	896	
225/45ZR16 93W RD	241850	7.0-7.5-8.5	20	10	23.9	8.9	11.1	1432	50	871	
245/45ZR16 94W	241870	7.5-8.0-9.0	22	10	24.7	9.6	11.4	1477	44	839	
215/40ZR16 86W RD	241690	7.0-7.5-8.5	18	10	22.8	8.6	10.6	1168	50	913	
225/40ZR16 89W RD	241670	7.5-8.0-9.0	19	10	23.1	9.1	10.7	1278	50	902	
205/50ZR17 93W RD	250150	5.5-6.5-7.5	22	10	25.1	8.4	11.7	1433	50	826	
215/50ZR17 91Y	242000	6.0-7.0-7.5	23	10	25.5	8.9	11.8	1356	44	816	
215/45ZR17 91W RD	241860	7.0-8.0	20	10	24.7	8.4	11.5	1355	50	843	
225/45ZR17 94W RD	241840	7.0-7.5-8.5	21	10	25.0	8.9	11.7	1477	50	828	
235/45ZR17 97W RD	241880	7.5-8.0-9.0	24	10	25.4	9.3	11.8	1609	50	818	
245/45ZR17 95W	241890	7.5-8.0-9.0	25	10	25.7	9.6	11.9	1521	44	807	
255/45ZR17 98Y	241900	8.0-8.5-9.5	27	10	26.1	10.0	12.0	1653	44	797	
205/40ZR17 84W RD	241700	7.0-7.5-8.0	19	10	23.5	8.4	11.0	1102	50	884	
215/40ZR17 87W RD	241710	7.0-7.5-8.5	20	10	23.8	8.6	11.2	1201	50	869	
235/40ZR17 94W RD	241720	8.0-8.5-9.5	21	10	24.4	9.5	11.4	1477	50	850	
245/40ZR17 95W RD	241730	8.0-8.5-9.5	22	10	24.7	9.8	11.5	1521	50	839	
255/40ZR17 94Y	241740	8.5-9.0-10.0	23	10	25.0	10.2	11.6	1477	44	830	
265/40ZR17 96Y	241750	9.0-9.5-10.5	26	10	25.4	10.7	11.8	1565	44	819	
275/40ZR17 98Y	247950	9.0-9.5-11.0	28	10	25.7	10.9	11.8	1653	44	814	

RD = Reinforced. Rim protector on all sizes. Bold designates measuring rim width.

When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph.

All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.



## PROXES T1-S™ ULTRA-HIGH PERFORMANCE RADIAL

**UTQG**  
All sizes  
280 AA A



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (32")	Inflated Dimension		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Price
					Overall Diameter (inch)	Overall Width (inch)					
245/35ZR17 91W RD	241600	8.0- <b>8.5</b> -9.5	22	10	23.8	9.8	11.2	1355	50	872	
235/50ZR18 97W	242010	6.5- <b>7.5</b> -8.5	28	10	27.3	9.7	12.6	1609	44	760	
245/45ZR18 96W	241910	7.5- <b>8.0</b> -9.0	28	10	26.7	9.6	12.4	1565	44	777	
255/45ZR18 99W	241920	8.0- <b>8.5</b> -9.5	28	10	27.1	10.0	12.5	1709	44	768	
225/40ZR18 92W RD	241760	7.5- <b>8.0</b> -9.0	22	10	25.1	9.1	11.8	1388	50	828	
235/40ZR18 95W RD	241770	8.0- <b>8.5</b> -9.5	23	10	25.4	9.5	11.9	1521	50	818	
245/40ZR18 93Y	247800	8.0- <b>8.5</b> -9.5	24	10	25.7	9.8	12.0	1433	44	807	
275/40ZR18 99Y	247910	9.0- <b>9.5</b> -11.0	28	10	26.7	10.9	12.3	1709	44	783	
285/40ZR18 101Y	247900	9.5- <b>10.0</b> -11.0	30	10	27.0	11.4	12.5	1819	44	770	
215/35ZR18 84W RD	241570	7.0- <b>7.5</b> -8.5	20	10	23.9	8.6	11.3	1102	50	856	
225/35ZR18 87Y RD	250520	7.5- <b>8.0</b> -9.0	20	10	24.2	9.1	11.5	1201	50	852	
245/35ZR18 88W	241610	8.0- <b>8.5</b> -9.5	23	10	24.8	9.8	11.6	1235	44	839	
255/35ZR18 90Y	250530	8.5- <b>9.0</b> -10.0	22	10	25.0	10.2	11.7	1323	44	830	
265/35ZR18 93W	241630	9.0- <b>9.5</b> -10.5	25	10	25.3	10.7	11.9	1433	44	819	
275/35ZR18 95Y	241640	9.0- <b>9.5</b> -11.0	26	10	25.6	10.9	12.0	1521	44	812	
285/35ZR18 97Y	241650	9.5- <b>10.0</b> -11.0	29	10	25.9	11.4	12.1	1609	44	802	
295/35ZR18 99Y	241660	10.0- <b>10.5</b> -11.5	30	10	26.1	11.9	12.2	1709	44	795	
245/40ZR19 98Y RD	247700	8.0- <b>8.5</b> -9.5	25	10	26.7	9.8	12.5	1653	50	775	
255/40ZR19 96Y	247710	8.5- <b>9.0</b> -10.0	25	10	27.1	10.2	12.7	1565	44	767	
215/35ZR19 85W RD	241590	7.0- <b>7.5</b> -8.5	21	10	24.9	8.6	11.8	1135	50	835	
235/35ZR19 91Y RD	248100	8.0- <b>8.5</b> -9.5	23	10	25.5	9.5	12.0	1356	50	817	
245/35ZR19 93Y RD	248110	8.0- <b>8.5</b> -9.5	24	10	25.8	9.8	12.2	1433	50	803	
255/35ZR19 96Y RD	248120	8.5- <b>9.0</b> -10.0	24	10	26.0	10.2	12.3	1565	50	793	
275/35ZR19 96Y	248150	9.0- <b>9.5</b> -11.0	28	10	26.6	10.9	12.4	1565	44	783	
265/30ZR19 93Y RD	248000	9.0- <b>9.5</b> -10.5	24	10	25.3	10.6	12.0	1433	50	818	
275/30ZR19 96Y RD	248010	9.0- <b>9.5</b> -11.0	26	10	25.6	10.9	12.1	1565	50	813	
245/35ZR20 95Y RD	248400	8.0- <b>8.5</b> -9.5	25	10	26.8	9.8	12.7	1521	50	773	
255/35ZR20 97Y RD	248410	8.5- <b>9.0</b> -10.0	25	10	27.0	10.2	12.8	1609	50	764	
275/30ZR20 97Y RD	248300	9.0- <b>9.5</b> -11.0	27	10	26.5	10.9	12.6	1609	50	779	

RD = Reinforced

Bold designates measuring rim width.

Rim protector on all sizes.

When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph.

All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.