

A048
Updated 6/27/05

Tire Size	Part No.	UTQG Rating	Unit Weight (lbs)	Measuring Rim Width	Approved Rim Width	Overall Width	Overall Diameter	Tread Width	Tread Depth (32/in)	Static Radius	Revs Per Mile	Max Load Cold Inflation Pressure	Type
ADVAN A048 - M Compound													
205/50R15 86V	04807	60/B/A	18.78	6.5	5.5-7.5	8.3	23.0	8.2	6	10.6	903	1168@51	BW
205/60R15 91H	04806	60/B/A	20.87	6.0	5.5-7.5	8.2	24.6	8.1	6	11.2	844	1365@51	BW
225/50R15 91V	04808	60/B/A	22.03	7.0	6.0-8.0	9.3	23.7	9.1	6	10.9	875	1356@51	BW
195/50R16 84W	04840	60/A/A	19.71	6.0	5.5-7.0	8.0	23.7	7.8	6	11.0	876	1102@51	BW
205/55R16 91W	04839	60/A/A	22.53	6.5	5.5-7.5	8.4	24.9	8.2	6	11.5	835	1356@51	BW
225/45R16 89W	04842	60/A/A	21.62	7.5	7.0-8.5	8.9	23.8	8.8	6	11.0	872	1279@51	BW
225/50R16 92W	04841	60/A/A	24.04	7.0	6.0-8.0	9.1	24.9	9.0	6	11.5	835	1389@51	BW
215/45R17 87W	04843	60/A/A	22.79	7.0	7.0-8.0	8.5	24.6	8.3	6	11.5	845	1201@51	BW
225/45R17 90W	04844	60/A/A	23.36	7.5	7.0-8.5	9.0	24.8	8.8	6	11.6	836	1323@51	BW
235/45R17 93W	04845	60/A/A	24.82	8.0	7.5-9.0	9.3	25.2	9.3	6	11.7	824	1433@51	BW

ADVAN A048 - MH Compound

195/50R16 84W	04810	60/A/A	19.79	6.0	5.5-7.0	8.0	23.7	7.8	6	11.0	876	1102@51	BW
205/55R16 91W	04809	60/A/A	22.62	6.5	5.5-7.5	8.4	24.9	8.2	6	11.5	835	1356@51	BW
225/45R16 89W	04812	60/A/A	21.47	7.5	7.0-8.5	8.9	23.8	8.8	6	11.0	872	1279@51	BW
225/50R16 92W	04811	60/A/A	24.09	7.0	6.0-8.0	9.1	24.9	9.0	6	11.5	835	1389@51	BW
215/45R17 87W	04813	60/A/A	22.88	7.0	7.0-8.0	8.5	24.6	8.3	6	11.5	845	1201@51	BW
225/45R17 90W	04814	60/A/A	23.20	7.5	7.0-8.5	8.9	24.9	8.8	6	11.6	835	1323@51	BW
235/45R17 93W	04815	60/A/A	25.04	8.0	7.5-9.0	9.3	25.2	9.0	6	11.7	824	1433@51	BW
245/40R17 91W	04816	60/A/A	25.31	8.5	8.0-9.5	9.8	24.8	9.7	6	11.5	839	1356@51	BW
255/40R17 94W	04817	60/A/A	26.48	9.0	8.5-10.0	10.3	25.0	10.0	6	11.6	829	1477@51	BW
225/40R18 88Y	04801	60/AA/A	22.88	8.0	7.5 - 9.0	9.1	25.0	8.5	6	11.7	829	1235@51	BW
235/40R18 91Y	04818	60/A/A	24.14	8.5	8.0-9.5	9.6	25.4	8.9	6	11.9	819	1356@51	BW
265/35R18 93Y	04802	60/AA/A	25.95	9.5	9.0 - 10.5	10.7	25.2	10.3	6	11.8	824	1433@51	BW
285/30R18 93Y	04803	60/AA/A	26.55	10.0	9.5 - 10.5	11.1	24.8	10.9	6	11.6	839	1433@51	BW
295/30R18 94Y	04819	60/A/A	27.01	10.5	10.0-11.0	11.6	24.9	11.1	6	11.7	833	1477@51	BW
315/30R18 98Y*	04820	60/A/A	29.64	11.0	10.5-11.5	12.3	25.4	11.8	6	11.9	818	1653@51	BW

*Available 3rd Quarter 2005