

**AVS dB S2 Updated
6/18/05 RO**

Tire Size	Part No.	UTQG Rating	Unit Weight (lbs)	Measuring Rim Width	Approved Rim Width	Overall Width	Overall Diameter	Tread Width	Tread Depth (32/in)	Static Radius	Revs Per Mile	Max Load Cold Inflation Pressure	Max Load Dual	Type
P205/60R15 90V	40233	320/A/A	19.56	6.0	5.5 - 7.5	8.2	24.7	6.5	10	11.3	841	1301 @44	-	BW
P205/65R15 92V	40234	320/A/A	21.71	6.0	5.5 - 7.5	8.2	25.5	6.5	10	11.6	815	1400 @44	-	BW
P215/65R15 95V	40236	320/A/A	22.56	6.5	6.0 - 7.5	8.8	25.9	6.5	10	11.8	801	1510 @44	-	BW
P225/60R15 95V	40239	320/A/A	23.12	6.5	6.0 - 8.0	9.0	25.6	7.2	10	11.6	810	1521 @44	-	BW
205/55ZR16 89W	40232	320/A/A	22.38	6.5	5.5 - 7.5	8.4	25.0	7.4	10	11.5	832	1279@44	-	BW
P215/60R16 94V	40235	320/A/A	22.69	6.5	6.0 - 7.5	8.6	26.1	6.9	10	12.0	794	1477@44	-	BW
225/50ZR16 92W	40237	320/A/A	23.60	7.0	6.0 - 8.0	9.0	25.0	8.3	10	11.5	832	1389@44	-	BW
225/55ZR16 95W	40238	320/A/A	24.69	7.0	6.0 - 8.0	9.1	25.8	8.1	11	11.8	805	1521@44	-	BW
P225/60ZR16 97W	40240	320/A/A	24.40	6.5	6.0 - 8.0	9.0	26.7	7.2	10	12.2	779	1609@44	-	BW
P245/50ZR16 96W	40244	320/A/A	26.55	7.5	7.0 - 8.5	9.9	25.7	9.0	11	11.8	809	1576@44	-	BW
225/45ZR17 91W	40252	320/A/A	25.01	7.5	7.0-8.5	8.9	25.0	8.3	10	11.6	829	1356@44	-	BW
235/45ZR17 93W	40241	320/A/A	24.84	8.0	7.5 - 9.0	9.5	25.3	8.7	10	11.7	820	1433@44	-	BW
P245/45ZR17 95W	40243	320/A/A	26.51	8.0	7.5 - 9.0	9.7	25.7	9.2	11	11.9	808	1521@44	-	BW
255/40ZR17 94W	40245	320/A/A	27.12	9.0	8.5 - 10.0	10.4	25.2	9.6	11	11.7	826	1477 @44	-	BW
P255/45ZR17 92W	40251	320/A/A	28.92	8.5	8.0 - 9.5	10.2	26.1	9.4	11	12.1	796	1389@44	-	BW
P275/40ZR17 98W	40248	320/A/A	29.10	9.5	9.0 - 11.0	11.1	25.7	10.4	10	11.9	807	1653 @44	-	BW
225/40ZR18 88W	40249	320/A/A	23.85	8.0	7.5 - 9.0	9.1	25.0	8.3	10	11.7	831	1235@44	-	BW
235/40ZR18 91W	40250	320/A/A	24.90	8.5	8.0 - 9.5	9.5	25.3	8.7	10	11.9	820	1356@44	-	BW
245/40ZR18 93W	40242	320/A/A	27.29	8.5	8.0 - 9.5	9.8	25.7	9.2	11	12.0	808	1433@44	-	BW
255/45ZR18 99W	40246	320/A/A	30.45	8.5	8.0 - 9.5	10.1	27.1	9.4	11	12.6	766	1709@44	-	BW
275/35ZR18 95W	40247	320/A/A	28.83	9.5	9.0 - 11.0	10.9	25.6	10.4	10	12.0	810	1521@44	-	BW